PERMIT FOR WELDING, CUTTING, OR BRAZING

1A. NAME OF EMERGENCY CONTACT	1B. TELEPHONE NUMBER
2. OFFICE ISSUING PERMIT	

3. LOCATION FOR PERMIT	A. BUILDING NAME	B. SPECIFIC LOCATION WITHIN BUILDING

4A. DATE OF WORK	5. SPECIAL NATURE OF WORK
4B. START TIME a.m. p.m.	
4C. STOP TIME a.m. p.m.	

6. ANTICIPATED HAZARD DUE TO WORK *(Safety/Health/Fire)*

7. LIST OF PROTECTIVE CLOTHING AND EQUIPMENT REQUIRED FOR WORK *(Include personal protection and public production)*

8. NAME OF PERSON PERFORMING WORK	9. NAME OF FIRE WATCH AT SITE

10. EMERGENCY PRECAUTIONS *(Include type of required fire extinguisher)*

11. PREWORK SITE INSPECTOR

A. SIGNATURE	B. NAME AND TITLE	C. DATE

12. PERMIT ISSUED BY

A. SIGNATURE	B. NAME AND TITLE	C. DATE

A. SIGNATURE OF POST-WORK CHECKUP INSPECTOR	13B. DATE

INSTRUCTIONS

General: A permit must be issued prior to starting welding, cutting, or brazing, regardless of GSA Service involved. All welding, cutting, or brazing shall adhere to the relevant OSHA Standards (29 CFR 1910, or 29 CFR 1926). Every item on the form must be completed. The lack of signatures or any item not completed voids the permit. If the work is performed for a confined space entry task, a copy of this form is posted next to GSA form 3625, Permit for Confined Space Entry. Both forms must be clearly posted outside the confined space. Prior approval from the regional Safety Environmental Management Office is mandatory if the permit is issued for a confined space entry task. Upon completion of the work, or when the expected stop time is reached (*which ever comes first)*, the completed permit is returned to the issuing authority for filling. The issuance of the permit in no way relieves a contractor of responsibility for an accident resulting from negligence with the work.

Item No.	**Action**
1A - 1B	Fill in the emergency name and telephone number in **red** *(preferred).*
4A - 4C	Permit is not valid 30 minuted prior to the end of the schedule work shift.
5	Validation for permit.
7	Protective devices also included screens and barricades for the protection of others.
8	Initial beside name to indicate knowledge and understanding of the form, its intended purpose, an safety precautions per OSHA Standard 29 CFR 1910, Subpart Q.
9	Initial besides name to indicate knowledge and understanding of the form and duties of a fire watch per OSHA Standard 29 CFR 1910, Subpart Q. The fire watch will not be the same person performing the work.
11	The pre-work inspection must be on the date of work before starting the operation. The supervisor in charge of the GSA employee performing the work or the Contracting Officer's representative conducts the inspection. The inspector ensures all combustibles are removed, covered, or protected.
12	Approves by the facility manager or authorized representative.
13	Conduct checkup 30 minutes after completion of work. Inspection should ensure the area is free of hazardous conditions.